



2016 TAYLOR X360M

TAYLOR

SERIAL #: SGE40841

- 11' ULTRA-VU 2-Stage Mast (143-in lowered height)
- 84-in pin-type "C" carriage
- 3.5-in X 8-in X 48-in pin mounted forks
- Cummins QSB 6.7L 173Hp Tier-4 Final diesel engine
- Donaldson dry-type air cleaner w/safety element & restriction indicator

CALL FOR PRICE

80
HOURS

36000 LB
CAPACITY

USED
CONDITION

SPECIFICATIONS

- 11' ULTRA-VU 2-Stage Mast (143-in lowered height)
- 84-in pin-type "C" carriage
- 3.5-in X 8-in X 48-in pin mounted forks
- Cummins QSB 6.7L 173Hp Tier-4 Final diesel engine
- Donaldson dry-type air cleaner w/safety element & restriction indicator (vertical air intake extension with TaylorMax Precleaner)
- Dana TC-32 3-speed powershift transmission
- Powertrain Protection System for engine and transmission
- Kessler D-81 planetary drive axle with wet disc brakes
- Taylor 300 welded steel steer axle (single hydraulic cylinder design with heavy-duty links from the cylinder ram directly to tapered roller bearing mounted spindles)
- Solid plate steer angle stop (more contact area than bolt heads which require adjustment)
- 12.00 X 20 – 24PR bias pneumatic drive and steer tires
- All-welded steel frame with 4 lifting eyes (lifting eyes not designed for level pick)
- Bolted counterweight
- Replaceable bolt-on steps and handrails
- Lockable Fuel Cap
- Sliding engine hood (on rollers), side service doors and removable floor panels open to expose drive train for ease of maintenance.

VIEW DETAILS